TOWN OF TROPHY CLUB
100 MUNICIPAL DRIVE, TROPHY CLUB, TEXAS 76262
Ofc: 682-831-4680 / Fax: 817-490-0705

COMPLIANCE PERMIT TO DISCHARGE SWIMMING POOL WATER

ORDINANCE NO. 2008-22

APPLICANT'S NAME: _____ PHONE: _____

APPLICANT'S ADDRESS: _____

CONTACT INFORMATION: _____

FILTRATION SYSTEM FOR POOL: _____

POOL SERVICE COMPANY: _____
Name Address Phone

By signature below, I hereby agree to comply with the provisions outlined in Town Ordinance 2008-22, which states in part:

1. **It shall be unlawful** for any Person owning, leasing, claiming, occupying or having supervision or control of any swimming pool to permit drainage of any swimming pool filter backwash and/or spent diatomaceous earth to the storm drainage system, to surface waters, or to any adjacent public or private property or to permit drainage of any swimming pool water to overflow onto a neighbor's property or to any surface waters.
2. **Draining on your own property** - The filter backwash water must be collected, contained and discharged to the sanitary sewer, if available, or to a vegetated area contained within your property, using sandbags or berms, as necessary. Cartridge filters should be rinsed in a sink, bathtub, or over a lawn or other vegetated area. Do not discharge onto saturated soils or areas where there has been a recent application of herbicides, pesticides, or fertilizers. Allow sufficient area to prevent the ponding of water. Collect materials (such as spent diatomaceous earth filter media) on a filter cloth placed over the discharge surface and then throw the filter cloth and filter media in the trash upon completion of filter cleaning.
3. **Draining dechlorinated pool water to the curb and gutter -** Prior to draining pool water, the pH level (between 6.5 and 8.5) shall be neutralized, and the chlorine or other disinfectant residual shall be at or below 0.01 parts per million (ppm). The chlorine may be allowed to naturally dissipate over 3 to 5 days or a chemical dechlorinator shall be added to reach the desired level for dechlorinization. Typical pool chlorine level is 2 to 4 ppm. Discharged pool water shall be free of any chemicals in toxic amounts, including but not limited to chlorine, bromine, hydrogen peroxide based products, copper, silver, algaecides, fungicides, soda ash, cyanuric acid and muriatic acid and shall be free of debris, algae, or vegetation. Pool or spa water treated with an ionizer or mineral purifiers shall **not** be discharged to the curb and gutter. If using a discharge hose to drain pool water, the hose shall be long enough to reach the curb to prevent soil erosion. This method shall only be allowed when there are no flooding problems on your street.
4. **Drain to sewer clean-out** – Residences without capabilities to drain and contain pool filter backwash onto their property, shall have their systems retrofitted to connect to the sanitary sewer collection system via their cleanout.

_____ _____
Signature of Permit Holder Date

_____ _____
Permitting Official Signature Date